



Dayliter Skylights

Warranty Information Package

The Brighter Idea!

Unit #1-20133 102 Avenue, Langley, BC V1M 4B4 Tel: 604-513-8018 Fax: 604-513-8019
Email: info@dayliter.com Website: www.dayliter.com



Specifications - Dayliter Model VCM Glass (Vinyl Curb Mounted)

Curb mounted thermally broken skylights shall be Dayliter VCM Model # _____ as manufactured by Dayliter Industries Ltd. in Langley, BC, Canada. The skylight shall be a factory assembled unit consisting of an extruded vinyl base frame with all corners fusion welded to ensure a watertight frame. The retaining cap shall consist of a T6063 extruded aluminum frame in (black) (brown) (white) (clear anodized) finish. The skylight shall be fastened together with stainless steel screws penetrating the side of the skylight.

Glazing materials shall be (double) (triple) flat glass in (LoE2) (LoE2 with Argon gas) (Heat Mirror TC88), with a uniform air space between.

The skylight assembly shall be airtight with no air paths to connect interior building to exterior elements. The condensation gutter with weep holes in all four corners shall be an integral part of the unit. A gasket shall be provided between all points of contact between glass surface and aluminum.

Specifications - Dayliter Model VCM Acrylic (Vinyl Curb Mounted)

Curb mounted thermally broken skylights shall be Dayliter model # VCM _____ as manufactured by Dayliter Industries Ltd. in Langley, BC, Canada. The skylight shall be a factory assembled unit consisting of an extruded vinyl base frame with all corners fusion welded to ensure a watertight frame. The retaining cap shall consist of a T6063 extruded aluminum frame in (black) (brown) (white) (clear anodized) finish. The skylight shall be fastened together with stainless steel screws penetrating the side of the skylight.

Glazing materials shall be (double) (triple) (acrylic) (polycarbonate) plastic (dome) (Ridgelite) (pyramid) in (clear) (bronze) (white) with a uniform air space between the domes and a perimeter moisture flange (*no-leak guarantee*) stretch formed into the top (acrylic) (polycarbonate) layer to eliminate water penetration.

The skylight assembly shall be airtight with no air paths to connect interior building to exterior elements. The condensation gutter with weep holes in all four corners shall be an integral part of the unit. A gasket shall be provided between all points of contact between (acrylic) (polycarbonate) surface and aluminum.

Specifications - Dayliter Model RDD (Roof Door)

Curb mounted thermally broken Roof Doors shall be Dayliter model # RDD _____ as manufactured by Dayliter Industries Ltd. in Langley, BC, Canada. The roof door shall be a factory assembled unit consisting of an extruded vinyl base frame with all corners fusion welded to ensure a watertight frame. Internal welded one piece aluminum frame with handle bar and lift mounts. All fabricated metal parts including hinges are white epoxy powder coated. All fasteners and internal latches are stainless steel. All units are equipped with triple hollow white frost free frames.

The retaining cap shall consist of a T6063 extruded aluminum frame in (black) (white) (brown) (clear anodized) finish. The skylight shall be fastened together with stainless steel screws penetrating the side of the roof door.

The Brighter Idea!



Glazing materials shall be double (clear) (bronze) acrylic dome with a uniform air space between the domes and a perimeter moisture flange (no-leak guarantee) stretch formed into the top acrylic layer to eliminate water penetration.

The roof door assembly shall be airtight with no air paths to connect interior building to exterior elements. The condensation gutter with weep holes in all four corners shall be an integral part of the unit. A gasket shall be provided between all points of contact between acrylic surface and aluminum.

Specifications - Dayliter Model ATCM Glass (Aluminum Thermally Broken Curb Mounted)

Curb mounted thermally broken skylights shall be Dayliter model # ATCM _____ as manufactured by Dayliter Industries Ltd. in Langley, BC, Canada. The skylight shall be a factory assembled unit consisting of a T6063 thermally broken extruded aluminum frame in black finish. All corners shall be welded. The retaining cap shall consist of a T6063 extruded aluminum frame in (black) (brown) (white) (clear anodized) finish. The skylight shall be fastened together with stainless steel screws penetrating the side of the skylight. The skylight shall be fastened together with stainless steel screws penetrating the side of the skylight.

Glazing materials shall be double glazed flat glass in (LoE2) (LoE2 with Argon gas) (Heat Mirror TC88), with a uniform air space between.

The skylight assembly shall be airtight with no air paths to connect interior building to exterior elements. The condensation gutter with weep holes in all four corners shall be an integral part of the unit. A gasket shall be provided between all points of contact between glass surface and aluminum.

Specifications - Dayliter Model ATCM Acrylic (Aluminum Thermally Broken Curb Mounted)

Curb mounted thermally broken skylights shall be Dayliter model # ATCM _____ as manufactured by Dayliter Industries Ltd. in Langley, BC, Canada. The skylight shall be a factory assembled unit consisting of a T6063 thermally broken extruded aluminum frame in (black) (brown) (white) (clear anodized) finish. All corners shall be welded. The skylight shall be fastened together with stainless steel screws penetrating the side of the skylight.

Glazing materials shall be double glazed (acrylic) (polycarbonate) (dome) (Ridgelite) (pyramid) in (clear) (white) (bronze) with a uniform air space between the domes and a perimeter moisture flange (no-leak guarantee) stretch formed into the top (acrylic) (polycarbonate) layer to eliminate water penetration.

The skylight assembly shall be airtight with no air paths to connect interior building to exterior elements. The condensation gutter with weep holes in all four corners shall be an integral part of the unit. A gasket shall be provided between all points of contact between (acrylic) (polycarbonate) surface and aluminum.

The Brighter Idea!



Dayliter Industries Ltd. does NOT warrantee the electric operators after they are purchased.

Due to the technical nature of the electrical components, directions and a manual are enclosed.

The Brighter Idea!

Unit #1-20133 102 Avenue, Langley, BC V1M 4B4 Tel: 604-513-8018 Fax: 604-513-8019
Email: info@dayliter.com Website: www.dayliter.com



Warranty

Dayliter Industries Ltd. warrants to the original owner that all technically superior Dayliter brand vinyl curb mount, aluminum curb mount and metal self-flash skylights will not leak when installed according to the recommended Dayliter installation instructions. This warranty is limited to defects in skylight design and workmanship.

Not covered under this warranty are yellowing of loss of light transmission cause by dirt, scratches, chemical pollutants, petroleum based cleaning solutions and breakage or damage caused by mishandling, abuse, falling objects, hailstorms or other severe weather conditions. During prolonged periods of humidity and temperature differentials acrylic skylights might accumulate moisture between the skins. Condensation between acrylic glazings must be expected from time to time, however, it will quickly dissipate with a change in the above conditions. Sealed Glass units are warranted for a period of 5 years directly from the glass manufacturer, unless otherwise guaranteed

The sole liability of Dayliter Industries Ltd. in respect of Dayliter brand skylights shall be limited to the replacement thereof. Dayliter Industries Ltd. shall have no liability under any circumstances for the cost of or associated with the removal of defective skylights, or shipping costs, or the installation of replacement skylights, or for any injury or damage to persons or property, or for indirect, incidental, or consequential damages or economic loss. Any addition or alteration to the Dayliter Skylight frame voids the warranty.

The Brighter Idea!